

The SPY II



The Spy II is an easy to use, portable alarm system that interfaces with existing customer radio systems for use in a variety of applications including stakeouts, construction site theft (ie copper wire), domestic violence, robberies and more. Provides a cost effective security solution for a wide variety of corporate, commercial, law enforcement and public safety applications.

TECHNICAL SPECIFICATIONS

The SPY II supports multiple sensors on two zones.

User recorded alarm messages are broadcast over radio.

One zone can be configured as a local speaker message.

Re-record your messages in seconds using front panel keypad.

Uses a variety of wireless sensors -motion, door, panic, tilt, glass break, bill trap and others.

Rechargeable gel-cell battery provides up to one week of battery life. System can be plugged into AC power to maintain continual battery charge.

Battery must be installed for operation.

Compatible with VHF, UHF, 800 and 900 Mhz radios, and virtually all models of digital trunking radio systems.

Range depends on current communication system. The system also supports a standard phone line. Optional cell phone module available.

Size: 10" x 8" x 4"
(not including handle and antenna)

Weight: 7.5 lbs.

Battery OK indicator light.

Full charge indicator light

Power ON/OFF Keyswitch

Record and Playback Buttons

Wireless Multichannel Alarm receiver

Entry/Exit Delay

SPY II